



Diversified's Aqua Seal DAS



FEATURES and BENEFITS

- Recommended as a temporary water-stop. Stops the intrusion of water into a piping sump or under dispenser containment while a permanent split repair of the fitting is performed.
- Use in the repair of leaking penetration fittings. Compatible with Weaver split repair products.
- Forms a barrier to hydrocarbons, water and other chemicals
- Dries tack free in 16 to 24 hours
- Easy to Dispense - use a standard off-the-shelf caulk gun.
- Cures Flexible but Tough

Product Matrix

Recommendations: Use protective gloves during application. Avoid skin and eye contact. Apply in ventilated area. Read warning below before usage.

Contains: Butyl Benzyl Phthalate, Polyurethane Polymer (mixture), Aromatic solvent, Calcium Carbonate, Carbon Black, Titanium Dioxide and iron oxides.

Federal Regulations: SARA Title III: (Section 313 Toxic Chemicals) and California Prop. 65 listed chemicals:

Chemical Name	CAS Number	Concentration	
Residual Toluene	26471-62-5	<0.2%	Volatile Organic Compounds (VOC) = <50 g/l (0.04 lb/gal)
Diisocyanate Monomer			Flash Point - 200° F (93° C)

The fill material is intended to form a stand alone temporary barrier to leaks. Should the flexible membranes of the penetration fitting be breached for any reason, DAS when properly installed will form a temporary barrier to water migration through the fitting.

Prior to installation, properly clean all surfaces of loose dust, dirt, rust, grease, mold release agents, oil and any material that will interfere with the bonding process. Diversified's DAS Aqua Seal is recommended for use with Weaver split repair products where water is present. DBC is supplied in cases of 12.

MSDS sheets are available in DPM's Master MSDS manual or DPM's Contractor Catalog, available from stocking distributors, on the Diversified's web site www.diversifiedproductsmfg.com and are available upon request directly from Diversified. All personnel should read and understand the safety recommendations. Keep uncured product away from children at all times.

DAS has a shelf life of 1 year from the date of filling. This date is located on the label of each cartridge set. Keep away from extreme heat, freezing and moisture. Proper storage temperature is between 50F and 90F. The components used in the DAS formulation have been specifically formulated to withstand low temperature applications. If the temperature of the material is below 32F, it is recommended to warm the product to a minimum of 60°F before application.



Chemical Compatibility Reference DAS

The data shown are the result of laboratory tests performed and reported by Diversified's materials suppliers. No performance warranty is

Table with 2 columns: Substance, Rating. Lists various chemicals and their compatibility ratings.

Table with 2 columns: Substance, Rating. Lists various chemicals and their compatibility ratings.

Table with 2 columns: Substance, Rating. Lists various chemicals and their compatibility ratings.

Key to Guide Codes

- 1- Product is suitable for use in immersion and/or splash and spillage conditions.
2- Product is suitable for occasional and intermittent contact for periods up to 72 hours in duration
3- Product is suitable for occasional and intermittent contact for short time periods with frequent washings.
S- Product may be stained by this chemical.
NR- Not recommended for this application

continued on next page



Chemical Compatibility Reference

DAS (cont.)

The data on this sheet is based on short term (30 - 60 days) laboratory immersion tests in a controlled environment (72-77° F). It is to be used only as a guide in selecting the proper sealant for a particular chemical environment. Many factors must be considered when choosing the correct product for an application, including:

- chemical or combination of chemicals exposure
- operating temperature
- temperature fluctuations
- type of substrate and its condition
- mechanical abuse
- the degree of protection required

Features

- **Proprietary formulated polysulfide**
- **Bonds to fiberglass sumps and pipes**
- **Adheres to Polyurethane and Alcryn flexible membranes**
- **Adheres to Galvanized Steel Pipes**
- **Gell Time: 15-20 minutes, Tack Free Time: 40-60 minutes**
- **Fuel compatible- Third Party Approved**
- **Remains highly flexible after curing**

Warranty

The technical data and any other printed information furnished by Diversified Products Mfg LLC is true and accurate to the best of our knowledge. DRP conforms to in-house quality control procedures and should be considered free of defects. Due to the wide range of applications of this product, it is impossible to assume responsibility for any errors in regard to application, coverage, workmanship, over-spray, or injuries resulting from the use of this product. Diversified Products Mfg LLC makes no warranty express or implied, of this product and shall not be liable for indirect or consequential damage in any event.