



DPM Diversified Bulkhead Fill
DBF II
STORE HORIZONTALLY

Installation Procedures

- Clean all surfaces to be filled with DBC Aerosol Cleaner
- Shake well before using
- Remove retainer nut and pop out "D" plugs
- Attach Static Mixing Wand, replace retainer nut and tighten
- Important: Polysulfide must be properly mixed
- Place cartridge in applicator gun DAG
- Hold tip of static mixer above gun while purging
- Actuate dispenser and dispense first ounce into a disposable container to verify uniform color of mixed polysulfide
- Dispense using slow even strokes into prepped clean, dry bulkhead fitting
- Gel Time: 15-20 minutes (80°F) Tack Free: 40-60 minutes (75°F)
- Penetration fittings may be hydrostatically tested 60 minutes after installation (75°F)

For Chemical Emergency, Spills, Leak Fire, Etc. Accident: Call Prevention Technologies 847-238-1100

Diversified Products Manufacturing, Inc. - Orville, California
Ph. 530-534-3968 Fx. 530-533-1361 or 888-534-3968
www.dpm-inc.com

For Industrial Use Only. Keep out of reach of Children. Read Safety Data Sheets and Installation Instructions before use.
Date Filled: **03/24/2009**

This material is UL listed as part of the installation procedures for Diversified penetration fittings.

Diversified Repair Paste
DPM **DRP**
STORE HORIZONTALLY

Installation Procedures

- Clean all surfaces to be filled with DBC Aerosol Cleaner
- Shake well before using
- Remove retainer nut and pop out "D" plugs
- Attach Static Mixing Wand, replace retainer nut and tighten
- Important: Polysulfide must be properly mixed
- Place cartridge in applicator gun DAG
- Hold tip of static mixer above gun while purging
- Actuate dispenser and dispense first ounce into a disposable container to verify uniform color of mixed polysulfide
- Dispense using slow even strokes into prepped clean and dry bulkhead fitting
- Gel Time: 15-20 minutes (80°F) Tack Free Time: 40-60 minutes (75°F)
- Penetration fittings may be hydrostatically tested 60 minutes after installation (75°F)

For Chemical Emergency, Spills, Leak Fire, Exposure or Accident: Call INFOTRAC 1-800-535-5053

For Industrial Use Only. Keep out of reach of Children. Read the Material Safety Sheets and Installation Instructions before using Product

Date Filled:

This material is UL Listed as part of the installation procedures for Environ penetration fittings. 20 oz. cartridge

DPM
Diversified Products Manufacturing, Inc.

Bulkhead Bonder
DBB V

50 ML

NON-CURABLE: Flammable liquid and vapor irritant. May cause allergic skin reactions. Read warning information on the product. Read Material Safety Data Sheet.

EMERGENCY Call
INFOTRAC 800-535-5053
Made in the USA

Manufactured by:
Diversified Products Manufacturing, Inc.
Orville, California, USA
(530) 534-3968

Guarantee
Diversified
warrants the
from the date
sole option
purchase
if it contains
workmanship
need it to be
defect within
constitute a
regards to the
has a shelf
of filling
THE FORE
OF ALL
OR H
TO THE
MESH
PARTICUL
Diversified
and Penetr
no event
to identify
Technology
special, and
other applic
the sale,
Manufactur
Diversified
Prevention
Manufactur